

TO BE CONSTRUCTED ON THIS ARRANGEMENT ESIGNER WITH CONSIDERATION TO THE LOAD				
EVENUT ASSEMBLIES. E ON THE EYEBOLT AND EYENUT ASSEMBLY 0331. AND DRESSED ON SITE. DRILLING AND SCARFING ESERVATIVES. R ARE TO BE COATED WITH GRAPHITE GREASE. ACCORDANCE WITH THE REQUIREMENTS OF NS125. EEN PARALLEL CABLES TO BE UTILISED AT SSION SLEEVES TO BE USED WHEN REQUIRED TO				В
				С
	250144	185198	A/R	
		59907	8	
P, 95-150mm <sup>2</sup> TO 95-150mm <sup>2</sup>		176591	8	
UIT CONDUCTOR SIZE)			4m	
nm² LV ABC)		H77222	8	
LATED (TO SUIT 95mm <sup>2</sup> LV ABC)	514053	H19073	8	D
150mm <sup>2</sup> LV ABC)	514053	150987		-
( 150)	513951	H38853	2	
/ ABC)		176651	4	
_V ABC)		176652		
	518081	177986	2	
	518082	H39655	2	-
ED (Ø22mm HOLE)	518081	H39231	4	
SUIT POLE)(SEE NOTE 3)	513653		 1	
ION	513988 DRG.NC	STOCK CODE	QTY	
CONSTRUCTION ROUGH TERMINATION ONDED CONSTRUCTION				F
514013		sheet 02	AMD 3	(
7		8		$\bigcirc$